

Specification Sheet		
Duradicat Coda	CL 0010 / CL 001	<u> </u>
Product Code	GL0910 / GL0911	
Product Description	Rebel Ladies Leather Shoe & Boot - Black Only	
		Materials
Upper Lining Inner Sole Toe Cap Eyelet Sole	High Quality Full Grain Cow Leather Breathable and Abrasion Resistant Tai-brella (equivalent to Cambrelle) Biagioli IBITECH 252 2mm Foam Insole Board Wide Profile Carbon Steel Slip-On Elasticated construction Dual Density Poly Urethane Sole	
Specifications		
Specifications		European Norm ISO EN20345-S1: 2004 Tested by Intertek - Approved Body Identification Number: 0362
Special Features		Easy elasticated slip-on design on shoes Boots have easy zip-up design Sole has 2-tiered heel design without compromising safety Dual-density PU Sole ensures maximum comfort and increased durability Available from Size 2 to Size 8 (Ladies)
Sole	Temperature Maximum Oil & Acid Resistance Slip Resistance Crack Resistance	90°C (degrees Celsius) Oil resistant PU Tested to Intertek PM144 2004 and meets these requirements. However, care should always be taken on wet or oily surfaces Tested to 30,000 flex cycles
Toe Cap Anti Static Properties		Tested to an impact resistance of 200 Joules Product is anti static. If application is life critical additional consultation with product expert is required. Electrical resistance can be significantly changed by flexing, contamination or moisture. Introduction of additional inner
Water Applications Sizing		sole reduces static resistance. Water resistant - Leather and PU combination Available from Size 2 to Size 8 (Ladies)
Lifespan		The application determines the length of service that should be achieved. Normal environments should provide 12 months' service, if appropriate care is taken. Refer Care guidelines
		Uses
Type of industry	Suitability	Comments
General	Highly suitable	
Construction	Widely used	Core in very vest areas required. Cumbasta would be mare suitable for vest area applications
Mining Detrochemical	Widely used Widely used	Care in very wet areas required. Gumboots would be more suitable for wet area applications Highly oil resistant but reference to chemical chart below is recommended
Petrochemical Engineering	Highly suitable	nightly of resistant but reference to chemical chart below is recommended
Engineering Power Generation	Widely used	
Agriculture	Highly suitable	
Food & Health	Widely used	Reference to Chemical resistance in cleaning areas may be necessary
Fishing & Allied Industries	Widely used	. 10.0. 5.100 to offermour robiotarios in dioaring aroas may be mocessary
Fabrication	Highly suitable	
Metal Industries	Widely used	Temperature limitations must be observed
Motor Industry	Highly suitable	
Glass Manufacturing and Fabrication	Widely used	Steel midsole advised to protect against glass penetration of the sole
Municipality	Highly suitable	
Waste Disposal	Widely used	Steel midsole advised to protect against penetration of the sole
Civil Contracting	Widely used	
Moving and Rigging	Highly suitable	
Forestry	Widely used	
Telecommunications	Widely used	In the appropriate job requirement
Contract Labour	Highly suitable	
Transport - Air, Road & Rail	Widely used	
Transport - Shipping	Widely used	

Transport - Shipping Widely used

It is important that the footwear selected must be suitable for the protection required by the wearer and the environment. If any uncertainty exists consultation between buyer and seller should be conducted to ensure that the correct footwear is selected. This application guide only offers very general advice and should be confirmed if there may be any concerns over potential protection from hazards of any form

Picture



